



Xerox® VersaLink® B620 Printer is built on Xerox® ConnectKey® Technology. For more information, go to **ConnectKey.com**.

System Specification			
Speed ¹	Black-and-White: Up to 65/61 ppm Letter/A4 Duplex Print Speed: 39/37 ipm Letter/A4		
Monthly Duty Cycle ²	Up to 300,000 pages		
Processor/Memory/ Hard Drive	Quad Core 1.2GHz /2 GB system memory/32GB eMMC/ Optional : 500+GB HDD		
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 2.0 direct print, NFC; Optional: WiFi®/WiFi® Direct with Xerox® Wireless Network Adapter		
Controller Features	Unified Address Book, Remote Control Panel, Configuration Cloning, Fleet Orchestrator, Configuration Watchdog, Security Dashboard		
Print			
Print Resolution	Up to 1200 x 1200 dpi		
First-Print-Out Time (as fast as)	4.0 seconds black-and-white		
Page Description Language	Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c/PCL® 6		
Print Features	Print from USB, Print from Cloud Repositories (Dropbox, OneDrive, and Google Drive), Encrypted Secure Print, Xerox® Earth Smart, Job Identification, Booklet Layout, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs, Print Around, Print on Alternate Paper		
Mobile and Cloud Ready			
Universal Print Ready	Microsoft Universal Print is a cloud print service, available to Microsoft 365 subscribers. It removes the need for on-site print servers and leverages the built-in drivers included in the Windows 10 and 11 PCs. You can enjoy the benefits of cloud hosting with a driverless setup for all Windows 10 and 11 clients. Utilize the Xerox Print Support App (Requires installation of Xerox Print and Scan Experience) to gain access to the Xerox Print Properties user interface.		
Mobile Connectivity	Optional: Wi-Fi Direct, Wi-Fi (802.11 b/g/n/ac) AirPrint (iOS) including iBeacon ³ (Bluetooth) for AirPrint Discovery		
Mobile Printing	Mopria® Print, Apple® AirPrint®, Xerox® Print Service (Android), @PrintByXerox App; Optional: Xerox® Workplace App (iOS/Android), iBeacon³ (Bluetooth) for AirPrint Discovery		
Mobile Apps and Xerox App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalize, print, convert, route, collaborate, and communicate. Visit xerox.com/WorkplaceApps to find apps by industry or workflow. Software and services: Xerox® DocuShare® Content Management Platform (xerox.com/ecm), XMPie® (xerox.com/XMPie), Xerox® Workplace Solutions (xerox.com/WorkplaceSolutions)		

Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional: Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution	
Cloud Identity Provider (IdP) Integration	Use your desktop, laptop, or mobile login credentials to log in to your VersaLink® MFPs with direct connections to popular cloud identity providers Okta, Ping Identity, and Microsoft® Azure	
Security		
Standard Features	802.1x, IPsec, HTTPS, SFTP and Encrypted Email, Firmware Verification, LogRhythm SIEM integration, Splunk SIEM integration, Network Authentication, SNM SHA-256 Hash Message Authentication, TL\$1.1/1.2/1.3, Security Certificates utilizing ECDSA, Automatic Self-signed Certificate, Cisco® Identity Services Engin (ISE) integration, Local Authentication (Internal Database), User Access, Port/IP/Domain Filtering, Audit Log, Access Control, User Permissions, Configuration Watchdog, Trusted Platform Module (TPM 2.0), Trusted Boot, AES 256-bit, FIPS 140-3, Job Level Encryption via HTTPS and Drivers, Signed Email, Common Crite Certification#, Encrypted Secure Print, Immediate Image Overwrite for optional hard disks ⁷	
Optional Features	Xerox® Card Reader Kits, 500+GB Hard Disk (AES 256-bit, FIPS 140-3) with multi-pass Image Overwrite ⁷ , Xerox® Workplace Cloud/Suite Print Management and Content Security; learn more at xerox.com/WorkplaceSolutions	
Print Management		
Standard Features	Xerox® Standard Accounting Feature (Print, Email), Network Accounting Enablement	
Optional Features	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox® Business Innovation Partners. Xerox® Virtual Print Management Service; learn more at xerox.com/PrintManagement	



The intuitive, tablet-like, 5-inch touch screen allows you to personalize your experience to get more done in fewer taps. Gain access to an array of productivity boosting apps through the Xerox App Gallery.

The 100-Sheet Bypass Tray handles media sizes from 3 x 5 in to 8.5 x 14 in/76.2 x 127 mm to 216 x 356 mm

The 550-Sheet Tray handles media sizes from 3.9 x 7.5 in to 8.5 x 14 in/98.4 x 191 mm to 216 x 356 mm



OPTIONAL PAPER FEEDING

550-Sheet Tray

Add up to 3 additional 550-sheet trays for a total paper capacity of 2,300 sheets.

2,100-Sheet Tray

Add an optional 2,100-sheet tray for even higher capacity. Can be combined with two optional 550-sheet trays. (Requires Caster Base)





OPTIONAL ACCESSORIES

Wireless Network Adapter enables wireless connectivity and includes support for Wi-Fi Direct.

The Caster Base allows for easy moving of floor-standing configurations.

Printer Stand

500+GB Hard Disk

Card Reader Kit



XEROX® EASY ASSIST APP

Xerox Easy Assist App provides easy set up and allows you to securely manage your device on the go right from your mobile phone, with real-time monitoring of printer performance and instant access to self-support services — all without the need for any IT support. Learn more at xerox.com/EasyAssist.



Device Specification			
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic, Croatian, Ukrainian		
Accessories			
Optional	Wireless Network Adapter 500+GB HDD Unicode Font Kit		
Electrical Requirements			
North America	Voltage: 110-127 VAC +/-10% Frequency: 50/60Hz +/- 3%, 11.6A		
Europe	Voltage: 220-240 VAC +/-10% Frequency: 50/60Hz +/- 3 %, 5.3A		
Power Consumption			
Running (Average)	Simplex 789W Duplex 551W		
Standby Mode	20 watts		
Auto Off/Sleep Mode	1.6 watts		
Warm-up (from Off)	As fast as 114 seconds		
Recovery from Sleep	As fast as 2.7 seconds		
Typical Energy Consumption	0.90kwh		
Operating Environment			
Required Temperature Range	50 to 90°F/ 10 to 32.2°C		
Required Relative Humidity	8 to 80% RH		
Sound Power Levels	Operating: 7.2 B(A) or less Standby: 3.2 B(A) or less		
Sound Pressure Levels	Operating: 56 db(A) or less Standby: 14 db(A) or less		
Dimensions and Weight	Packaged	Unpackaged	
Base Configuration	Width: 21/7 in/550 mm Depth: 25.6 in/650 mm Height: 22.2 in/565 mm Weight: 65.8 lb/29.9 kg	Width: 16.85 in/428 mm Depth: 20.1 in/510 mm Height: 17.5 in/445 mm Weight: 56.0 lb/25.4 kg	
550-Sheet Tray	Width: 19.6 in/498 mm Depth: 23.5 in/598 mm Height: 7.7 in/196 mm Weight: 18.1 lb/8.2 kg	Width: 16.9 in/428 mm Depth: 20.1 in/510 mm Height: 4.3 in/110 mm Weight: 13.5 lb/6.2 kg	
2,100-Sheet Tray	Width: 21.4 in/543.49 mm Depth: 23.5 in/598 mm Height: 18.9 in/479 mm Weight: 20.4 lb/6.8 kg	Width: 16.9 in/428 mm Depth: 20.1 in/510 mm Height: 13.8 in/350 mm Weight: 39 lb/17.7 kg	
Caster Base	Width: 34.0 in/864 mm Depth: 35.0 in/889 mm Height: 9.0 in/229 mm Weight: 63.1 lb/28.6 kg	Width: 20.5 in/521 mm Depth: 27.3 in/693 mm Height: 5.0 in/126 mm Weight: 17.4 lb/7.9 kg	
Printer Stand	Width: 20.7 in/525 mm Depth: 22.2 in/565 mm Height: 9.2 in/235 mm Weight: 37.7 lb/17.1 kg	Width: 18.2 in/463 mm Depth: 20 in/510 mm Height: 17.3 in/440 mm Weight: 32.7 lb/14.8 kg	
System Certifications/Regulatory Compliance			
Certifications	To view the latest list of certifications, go to xerox.com/OfficeCertificat	ions	

Paper Handling			
Bypass Tray (Standard)			
Capacity ⁴	100 sheets		
Sizes	Custom Sizes: 3 x 5 in to 8.5 x 14 in/76.2 x 127 mm to 216 x 356 mm		
Weights	16 to 47 lb bond/60 to 176 gsm		
Mediα Types	Bond Card Stock Custom Envelopes Glossy Card Stock Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted Recycled		
Trays 1 (Standard)			
Capacity ⁴	550 sheets		
Sizes	Tray 1: Custom Sizes: 3.9 x 7.5 in to 8.5 x 14 in/98.4 x 191 mm to 216 x 356 mm		
Weights Mediα Types	16 to 47 lb bond/60 to 176 gsm Bond		
	Card Stock Custom Envelopes Glossy Card Stock Hole Punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted Recycled		
Additional Trays (Optional)			
Capacity ⁴	550-Sheet Tray: Add up to 3 additional 550-sheet trays 2,100-Sheet Tray: Add an optional 2,100-sheet tray. Can be combined with up to two optional 550-sheet trays. (Requires Caster Base)		
Sizes	550-Sheet Tray: 3.9 x 7.5 in to 8.5 x 14 in/98 x 191 mm to 216 x 356 mm 2100-Sheet Tray: 8.27 x 5.83 in to 8.5 x 14 in/210 x 148 mm to 216 x 356 mm		
Weights	16 to 47 lb bond/60 to 176 gsm		
Media Types	Bond Card Stock Custom Envelopes Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted Recycled		
Total Capacity			
Device Total Capacity ⁴	Base Model: 650 sheets 550-Sheet Tray: Add up to 3 additional 550-sheet trays for a total capacity of 2,300 sheets. 2,100-Sheet Tray: Add an optional 2,100-sheet tray for a total capacity of 2,750 sheets. Can be combined with up to two optional 550-sheet trays for a total capacity of 3,850 sheets. (Requires Caster Base) Paper Output: 550 sheets		

Print		
Resolution (up to)	1200 x 1200 dpi	
Print Features	Application Defaults Banner Sheet Enable/Disable Booklet Layout Cover Selection Fit to New Paper Size Hold All Jobs Image Options (Resolution (Enhanced, High)) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) Layout/Watermark N-up (up to 16 pages per sheet) Paper Selection by Attribute Print From Cloud Repositories (Dropbox, OneDrive, and Google Drive) Sample Set Saved Job Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) Two-sided Printing (as default) User Permissions	
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, PCL	
Operating Systems	Note: For latest supported versions please visit our Drivers & Downloads page and specify your device at support.xerox.com Windows Server 2012 and R2 (64-bit) Windows Server 2016 (64-bit) Windows Server 2019 (64-bit) Fedora® Core Ubuntu® Windows Server 2022 (64-bit) macOS 12 Monterey, 13 Ventura, 14 Sonoma	
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD Microsoft Windows Networking over IP Support for Microsoft Universal Print Bonjour® AirPrint® Mopria® IPv6 Most protocols not in use can be disabled	
Font Capability	PCL: 93 scalable fonts, line printer, and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts	
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade, and manage Xerox® Devices and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end-users, reducing the number of support calls and simplifying print services management	
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy, and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos®, and others	

Security

Features

- Audit Log
- Cisco® Identity Services Engine (ISE) compatible
- Configuration Watchdog (Monitors and remediates security settings in the following areas):
- 802.1x
- Admin Password Reset
- Audit Log
- Automatic Software Upgrade
- Email Alerts
- FIPS 140
- Hold All Jobs
- Immediate Job Overwrite⁷
- Installation Policies
- PII Login Name
- PostScript Passwords
- Remote Services Enablement
- Remote Start (TWAIN)
- Reprint Saved Jobs
- Scheduled Disk Overwrite⁷
- Secure Print Device Policies
- SIEM
- SNMP
- System Timeout
- USB (Print from USB)
- USB Port Management
- User Data Encryption
- Expanded Authentication

- Digitally signed PDF (when using Smart Card authentication)
 Encrypted/Password Protected PDF (when using Email Templates only)
 FIPS 140 256 bit Hard Disk Encryption², TLS 1.1/1.2/1.3, IPPS, HTTPS, SFTP, SNMPv3
- Immediate Image Overwrite/Securely delete jobs using approved algorithms⁷
- Local Authentication (internal database)
- Network authentication to access device and/or device services via Kerberos (UNIX/Windows Server 2008), SMB (Windows Server 2008,
- Windows server 2012), NDS, LDAP authentication
- On Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk⁷ - Smart Card authentication – 144k CAC/PIV Card Support (2048 bit certificate key)/.NET
- Secure Data
- Secure Print (up to 10 digit PIN or Network Authentication)
- Expanded Authorization
- Authorization per user per service
- SA access based on network credentials
- Secure Network Access
- User Permissions required to access Print and Print Features (e.g., time restrictions) reflects in the print driver • Hide Print Job Names
- IP Filter, IPsec, IPv6, TLS V1.0, V1.2, V1.3, SNMP V1/V2/V3, HTTPs, 802.1X, SFTP
- Port disablement including USB ports
- LogRhythm SIEM integration
- Splunk SIEM integration

Device Management			
Administrative Protocols	DHCP, BOOTP, SNMP, SLPv2, HTTP, HTTPS, AutoIP (Self Assigned Address)/DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS, Bonjour, syslog (for SIEM)		
Xerox Easy Assist App	Xerox Easy Assist App provides easy set up and allows you to securely manage your device on the go right from your mobile phone, with real-time monitoring of printer performance and instant access to self-support services — all without the need for any IT support. Learn more at xerox.com/EasyAssist		
Management Support	SNMP Version 1. SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System-Power MIB, Fleet Orchestrator, Configuration Watchdog		
Xerox® CentreWare® Web Software	A Web-based server application for network administrators that permits Web browser-based device management from any workstation, whether running on Windows, UNIX, or any other operating system: • Works with any SNMP-managed printer from any manufacturer • Remote configuration of SNMP v3 • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management • Auto-detect Xerox® CentreWare® Web server and download configurations files for touchless remote install		
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor, and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: • Device monitoring and troubleshooting • Remote configuration of SNMP v3 • Extensive reporting and discovery of new devices • Usage collection, chargeback, and billing capabilities • Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install		
Xerox® Workplace Cloud	Remote management to set and audit device configuration data with Xerox® Workplace Cloud, eliminating the need for an on-site server		
Fleet Orchestrator	Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files, and 1-Touch App files. Auto-assembly feature allows a new VersaLink® to automatically set itself up on the network to be automatically configured		
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Program, provides seamless connectivity between SAP systems and your Xerox® Printers and Multifunction Printers. As an SAP customer, you benefit from having SAP-certified Xerox® Device types available right from SAP's online delivery model. SAP-certified device types for Xerox® Printers and Multifunction Printers are available to download. office.xerox.com/Software-Solutions		
Xerox [®] Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Center Barcode Fonts. Information available at office.xerox.com/Software-Solutions		
Xerox® Embedded Web Serve	er – Integrated Device Web Pages Provided by the Device		
Device Status	Web server embedded in Network Controller: • Tray status/contents • Consumables status • Alerts • Remote Control Panel		
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPEG, TXT, PRN Output feature selection (2-sided, collate, orientation, output destination) Delivery options (Immediate, sample set, delay, secure, save job for reprint)		
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator		
Browsers	Brave Browser Chrome Microsoft Edge Mozilla Firefox Opera Safari		
Support	Install print drivers and online support available via support.xerox.com		
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic, Ukrainian, Croatian		
Remote Services			
Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for tracking and billing of Xerox® Device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time		
Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® Devices based on actual usage, eliminating the need to manually manage supplies inventory		
Workplace Cloud Direct	Embedded device agent technology allows your printer to connect directly with Xerox Workplace Cloud for a zero network footprint offering a 'true' cloud-only Print Management and Mobile solution		

Accounting				
Xerox® Standard Accounting Feature				
Tracking	Print and Email usage			
Accounting	Up to 2,495 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group Accounts (Department)			
Features	Administrator can manage the feature via the Web User Interface or device control panel in tools Administrator has the ability to import or export User Accounts, Group Accounts, General Accounts, and User Limits via an industry standard CSV file			
Accounting Options – Netwo	rk Accounting (Allows central server to manage all accounting)			
Enhanced network accounting with up-to-the-minute data on how the system is being used Comprehensive management and enterprise-scale tracking and reporting of device usage of print Numerous solutions are available through Xerox Alliance Partners. For details, visit xerox.com Security enhancements with the addition of HTTPS protocol support Device requests account authentication from third-party server enabling larger databases of users and accounts Accept Authentication Login at control panel and pass to third-party Networking Account Interface with third-party accounting terminal for accounting user interface				
Installation Considerations				
Clear area around the device is necessary for access and ventilation.	Top: 3 in/76 mm Rear: 6 in/152 mm Left: 3 in/76 mm Right: 3 in/76 mm Front: 16 in/406 mm			
What's In The Box				
All items contained in the box:	VersaLink® B620 Printer AC Power Cord Installation Guide Product Information Flyer Product Safety Sheet Software Update Flyer Software and Documentation CD Black Print Cartridge: 10,000 page capacity ⁵			
Xerox® Supplies and Accesso	ries	North America and Europe*	All other regions	
Genuine Xerox Black Stando	ard Capacity Toner Cartridge, Xerox® VersaLink® B620 Printer (10,000 Pages) ⁵	006R04668	N/A	
Genuine Xerox Black High-C	apacity Toner Cartridge, Xerox® VersaLink® B620 Printer (25,000 Pages)5	006R04669**	006R04672	
Genuine Xerox Black Extra High-Capacity Toner Cartridge, Xerox® VersaLink® B620 Printer (42,000 Pages) ⁵		006R04670	006R04673	
Genuine Xerox Black Imaging Kit, Xerox® VersaLink® B620 Printer (150,000 Pages) ⁶		013R00699	013R00699	
Optional Accessories				
550-Sheet Tray		097N02445		
2,100-Sheet Tray		097N02446		
500+GB Hard Disk		097N02443		
Wireless Network Adapter		097N02444		
Printer Stand		097S05244		
Caster Base		097N02447		

^{*} North America (NA): U.S., Canada

Europe (XE): U.K., France, Germany, Spain, Italy, Netherlands, Belgium, Norway, Sweden, Finland, Denmark, Iceland, Luxembourg, Austria, Switzerland, Portugal, Ireland Andorra, Azores, Corsica, Greenland, Iceland, Lichtenstein, Luxembourg, Madeira, San Marino

Return spent imaging supplies through the Xerox® Green World Alliance® collection/reuse/recycling program.8 Visit xerox.com/About-Xerox/Recycling.

For more information, visit us at xerox.com/Office.

© 2023 Xerox Corporation. All rights reserved. Xerox®, CentreWare®, ConnectKey®, DocuShare®, Global Print Driver®, Green World Alliance® and Versal.ink® are trademarks of Xerox Corporation in the United States and/or other countries. As an ENERGY STAR® partner, Xerox Corporation has determined that thisproduct meets the ENERGY STAR guidelines for energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered U.S. marks. Apple, AirPrint, Bonjour and iBeacon, are trademarks of Apple, Inc., registered in the U.S. and other countries and regions. The Bluetooth® word mark is a registered trademark owned by the Bluetooth SIG, Inc. and any use of such marks by Xerox is under license. Mopria[™] is a registered and/or unregistered trademark of Mopria Alliance, Inc. in the United States and other countries. Unauthorized use is strictly prohibited. Wi-Fi® and Wi-Fi Direct® are registered trademarks of Wi-Fi Alliance®. The information in this brochure is subject to change without notice. 10/23 TSK-3741 BR39308 V62SS-02UA



^{*} Available in North America only

[#] Currently undergoing evaluation

Declared in accordance with ISO/IEC 24734.

² Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

³ Wireless Network Adapter is required for iBeacon.

⁴ Paper capacities are based on 20 lb/75 gsm stock; capacities will vary with different weight stocks.

⁵ Average standard pages. Declared in accordance with ISO/IEC 19752. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes, and image quality set-points.

 $^{^6}$ Average drum yield is based on a run length of 5 pages of 8.5 x 11 in/A4 LEF 7 Requires 500+GB Hard Disk

⁸ Not all countries support Green World Alliance. Please check local legislation