

New

Poly Studio V52 USB Video Bar

A09D4AA

For the latest in advanced conferencing tech coupled with USB simplicity, Poly Studio V52 Premium USB Video Bar has joined the call. Make effortless, crystal-clear connections in any medium-sized room thanks to striking visuals and next-gen AI features.

Active between

1. apr. 2024 - 31. maj 2027

Cena seznama 2.761,95 €

[Additional Price Information](#) →



Specifications

Barvno	White
Brezžične tehnologije	Wi-Fi 802.11a/b/g/n/ac/ax (MIMO) Multi-channel Concurrency; Bluetooth® 5.0 (audio sink not supported)
Diagonalno vidno polje (dFoV)	110°
Doseg kamere (metrični sistem)	Up to 6.1 m
Fizična varnost	Standard Kensington lock slot
Funkcije pokrovčka objektiv	Attachable
Garancija	Poly standard one-year limited warranty
Hitrost sličic video posnetka	5-60 fps (up to 4K resolution at 15 fps in call)
Interoperabilnost	All cloud service providers through Poly Video App mode; USB Device mode
Izhodna moč zvočnika	1 x 20 W (RMS); 1 x 40 W (maximum)
Koda UNSPSC	45121520
Ločljivost fotoaparata	2160p, 4K UHD (3840 x 2160)
Ločljivost videoposnetkov ljudi	4K, 30 fps (TX and RX) from 2048 Kbps; 1080p, 60 fps from 1740 Kbps; 1080p, 30 fps from 1024 Kbps; 720p, 60 fps from 832 Kbps; 720p, 30 fps from 512 Kbps
Ločljivost videoposnetkov vsebine (vhodna)	UHD (3840 x 2160); HD (1920 x 1080); WSXGA+ (1680 x 1050); UXGA (1600 x 1200); SXGA (1280 x 1024); WXGA (1280 x 768); HD (1280 x 720); XGA (1024 x 768); SVGA (800 x 600)
Napajanje	65 BTU h; 37 VA, 120 V 60 Hz; 37 VA, 230 V 50/60 Hz
Občutljivost (zvočnik)	79 dB
Obseg vlažnosti za delovanje	15 to 80%
Omrežne možnosti	IPv4; IPv6; 1x 10/100/1G Ethernet; Web proxy support: basic, digest, and NTLM

Potrebna je registracija	No
Priporočena vlažnost za mirovanje	5 to 95%
Programska oprema za upravljanje	Poly Lens
Razpon sprejema mikrofona (metrični sistem)	Up to 6.09 m
Skupna ločljivost fotoaparata (v milijonih slikovnih pik)	20 MP
Standardi za videoposnetke	UVC 1.1, up to 4K NV12 30 fps, 4K MJPEG 30 fps
Standardi za zvok	Up to 48 kHz/16 bit/Stereo; UAC 2.0
Tehnologija pametne kamere	Poly DirectorAI with speaker framing; People framing; Group framing; Presenter tracking; DirectorAI perimeter
Temperatura pri nedelovanju – v stopinjah Celzija	-40 to 70 °C
Temperaturni obseg delovanja	32 to 104 °F
Upravljanje varnosti	AES 128 bits encryption; AES 256 bits encryption; Authenticated access to admin menus, web interface, and APIs; BFCP; Local account password policy configuration
Višina delovanja	4,877 m
Vodoravno vidno polje	95°
Vrata	1 HDMI-in 2.0 (video and audio); 2 HDMI-out 2.0 (video); 1 USB Type-C® 5Gbps signaling rate; 2 USB Type-A 5Gbps signaling rate; 1 RJ-45; 1 line in (optional microphone)
Vrsta fotoaparata	Single-lens
Vrsta mikrofona	Two MEMS microphones; Two second-order microphones
Vrsta napajanja	External
Vrsta zvočnika	Stereo speakers
Vsebina škatle	Ethernet cable; Monitor clamp; Privacy cover; AC power adapter; HDMI cable; USB Type-A to USB Type-C® cable; Poly Studio V52
Zmožnost povečave	5x digital
Zvočne funkcije	Full duplex audio; Acoustic echo cancellation; Poly NoiseBlockAI technology; Poly Acoustic Fence technology

Legal disclaimer